

## GMC

<u>SPEC</u>	<u>CODE</u>	<u>RED</u>	<u>WHITE</u>	<u>COMMENTS</u>
GM4342M	10D24	N/A	24	BAKE IF REQUESTED/REQUIRED
GM4342M	10U8	8	N/A	BAKE IF REQUESTED/REQUIRED
GM4342M	15U24	24	N/A	BAKE IF REQUESTED/REQUIRED
GM4342M	20D24	N/A	24	BAKE IF REQUESTED/REQUIRED
GM4342M	20D48	N/A	48	BAKE IF REQUESTED/REQUIRED
GM4342M	20D72	N/A	72	BAKE IF REQUESTED/REQUIRED
GM4342M	20D96	N/A	96	BAKE IF REQUESTED/REQUIRED
GM4342M	20K24	N/A	24	BAKE IF REQUESTED/REQUIRED
GM4342M	20K32	N/A	32	BAKE IF REQUESTED/REQUIRED
GM4342M	20K8	N/A	8	BAKE IF REQUESTED/REQUIRED
GM4342M	20L24	N/A	24	BAKE IF REQUESTED/REQUIRED
GM4342M	20L8	N/A	8	BAKE IF REQUESTED/REQUIRED
GM4342M	20U32	32	N/A	BAKE IF REQUESTED/REQUIRED
GM4342M	20Z24	N/A	24	BAKE IF REQUESTED/REQUIRED
GM4342M	20Z8	N/A	8	BAKE IF REQUESTED/REQUIRED
GM4342M	30D48	N/A	48	BAKE IF REQUESTED/REQUIRED
GM4342M	30D72	N/A	72	BAKE IF REQUESTED/REQUIRED
GM4342M	30D96	N/A	96	BAKE IF REQUESTED/REQUIRED
GM4342M	30U40	40	N/A	BAKE IF REQUESTED/REQUIRED
GM4342M	50D72	N/A	72	BAKE IF REQUESTED/REQUIRED
GM4342M	50D96	N/A	96	BAKE IF REQUESTED/REQUIRED
GM4342M	50K48	N/A	48	BAKE IF REQUESTED/REQUIRED
GM4342M	50U48	48	N/A	BAKE IF REQUESTED/REQUIRED
GM4345M	10D192/96*	192	96	BAKE IF REQUESTED/REQUIRED. * BASED ON GM EUROPE SPECIFICATIONS
GM4345M	12D144/48	144	48	BAKE IF REQUESTED/REQUIRED
GM4345M	12D168/72	168	72	BAKE IF REQUESTED/REQUIRED
GM4345M	12D192/96	192	96	BAKE IF REQUESTED/REQUIRED
GM4345M	12E480/72			
GM4345M	12K120/0	120	0	BAKE IF REQUESTED/REQUIRED
GM4345M	12U96/0	96	N/A	BAKE IF REQUESTED/REQUIRED

**GMC**

<u>SPEC</u>	<u>CODE</u>	<u>RED</u>	<u>WHITE</u>	<u>COMMENTS</u>
GM4345M	15B0/144*	0	144	BAKE IF REQUESTED/REQUIRED. * BASED ON GM EUROPE SPECIFICATIONS. ** CANNOT DO INTERNAL DRIVE THREADED FASTENERS.
GM4345M	15D240/0*	240	0	BAKE IF REQUESTED/REQUIRED. * BASED ON GM EUROPE SPECIFICATIONS. ** SPEC CALLS FOR YELLOW-BROWN OR OLIVE DRAB, WE CANNOT MEET THE SALT SPRAY REQUIREMENTS WITH YELLOW-BROWN.
GM4345M	15K144/0*	144	0	BAKE IF REQUESTED/REQUIRED. * BASED ON GM EUROPE SPECIFICATIONS
GM4345M	15U12/0*	120	N/A	BAKE IF REQUESTED/REQUIRED. * BASED ON GM EUROPE SPECIFICATIONS
GM4345M	3D72/48	72	48	BAKE IF REQUESTED/REQUIRED
GM4345M	3K32/8*	32	8	BAKE IF REQUESTED/REQUIRED. * BASED ON GM EUROPE SPECIFICATIONS
GM4345M	3U24/0	24	N/A	BAKE IF REQUESTED/REQUIRED
GM4345M	6D120/72	120	72	BAKE IF REQUESTED/REQUIRED
GM4345M	6D144/96	144	96	BAKE IF REQUESTED/REQUIRED
GM4345M	6D96/48	96	48	BAKE IF REQUESTED/REQUIRED
GM4345M	6E240/72			
GM4345M	6K56/8*	56	8	BAKE IF REQUESTED/REQUIRED. * BASED ON GM EUROPE SPECIFICATIONS
GM4345M	6U48/0	48	N/A	BAKE IF REQUESTED/REQUIRED
GM4345M	9B0/72*	0	72	BAKE IF REQUESTED/REQUIRED. * BASED ON GM EUROPE SPECIFICATIONS. ** CANNOT DO INTERNAL DRIVE THREADED FASTENERS.
GM4345M	9D120/48	120	48	BAKE IF REQUESTED/REQUIRED
GM4345M	9D144/72	144	72	BAKE IF REQUESTED/REQUIRED
GM4345M	9D168/96	168	96	BAKE IF REQUESTED/REQUIRED
GM4345M	9E336/72			
GM4345M	9K96/0	96	0	BAKE IF REQUESTED/REQUIRED

## GMC

<u>SPEC</u>	<u>CODE</u>	<u>RED</u>	<u>WHITE</u>	<u>COMMENTS</u>
GM4345M	9U72/0	72	N/A	BAKE IF REQUESTED/REQUIRED
GM4435M	CODE A	72	N/A	
GM4435M	CODE B	72	N/A	
GM4435M	CODE D	N/A	N/A	
GM4435M	CODE E	24	N/A	
GM4435M	CODE G			
GM6035M				
GM6047M	CODE G			
GM6047M		168	N/A	
GM6111M				
GM6138M		500	48	
GM6173M		480	N/A	
GM6173M (HEX FREE)		480	N/A	
GM6173M BLACK		480	N/A	
GM6173M BLACK (HEX FREE)		480	N/A	
GM6174M		168	N/A	BAKE IF REQUESTED/REQUIRED
GM6280M SN-ZN (TIN-ZINC)				
GM6280M ZN-CO (ZINC-COBALT)				
GM6280M ZN-FE (ZINC-IRON)				
GM6280M ZN-NI (ZINC-NICKEL) CLEAR		240	N/A	BAKE IF REQUESTED/REQUIRED
GM6280M ZN-NI (ZINC-NICKEL) YELLOW		500	N/A	BAKE IF REQUESTED/REQUIRED
GM7111M				
GM7112M				
GM7113M				
GM7114M				
GM7153M		240	120	
GME 00 255 C		480	N/A	
GME 00 255 F		480	N/A	

**GMC**

<u>SPEC</u>	<u>CODE</u>	<u>RED</u>	<u>WHITE</u>	<u>COMMENTS</u>
GMW14		480	N/A	
GMW14 BLACK		480	N/A	
GMW3044	12U96/0	96	N/A	*TRICHROMAX 120 CLEAR NEEDED TO MEET SS REQ. BAKE IF REQUESTED/REQUIRED
GMW3044	15K360/120	360	120	BAKE IF REQUESTED/REQUIRED
GMW3044	15U12/0	120	N/A	*TRICHROMAX 120 CLEAR NEEDED TO MEET SS REQ. BAKE IF REQUESTED/REQUIRED
GMW3044	3U24/0	24	N/A	*TRICHROMAX 120 CLEAR NEEDED TO MEET SS REQ. BAKE IF REQUESTED/REQUIRED
GMW3044	6K96/48	96	48	BAKE IF REQUESTED/REQUIRED
GMW3044	6U48/0	48	N/A	*TRICHROMAX 120 CLEAR NEEDED TO MEET SS REQ. BAKE IF REQUESTED/REQUIRED
GMW3044	8K240/120	240	120	BAKE IF REQUESTED/REQUIRED
GMW3044	9U72/0	72	N/A	*TRICHROMAX 120 CLEAR NEEDED TO MEET SS REQ. BAKE IF REQUESTED/REQUIRED
GMW3044	BLACK			
GMW3044	SUFFIX "G"	N/A	N/A	
GMW3044	SUFFIX "N"	N/A	N/A	IF NO SUFFIX TO THE CODE IS USED THE PROVISION OF SUFFIX "N" SHALL APPLY
GMW3044	SUFFIX "T"			
GMW3044	SUFFIX "Y"	N/A	N/A	
GMW3044	YELLOW*	500**	120**	* WHEN YELLOW IS REQUESTED. ** MAX HOURS FOR NOKROM Y.
GMW3179	CODE A	24	N/A	
GMW3179	CODE B	72	N/A	
GMW3179	CODE D	1*	N/A	* 1 HOUR SALT SPRAY REQUIREMENT TO BE USED AS A REFEREE TEST TO VERIFY COMPLETE PHOS COVERAGE.
GMW3179	CODE G			

# GMC

<u>SPEC</u>	<u>CODE</u>	<u>RED</u>	<u>WHITE</u>	<u>COMMENTS</u>
GMW3179	CODE W	24	N/A	
GMW3200				
GMW3359		480	N/A	
GMW3359 BLACK		480	N/A	
GMW4205		480	48	
GMW4700 ZN-CO (ZINC-COBALT)				
GMW4700 ZN-CO-FE (ZINC-COBALT-IRON)				
GMW4700 ZN-FE (ZINC-IRON)				
GMW4700 ZN-NI (ZINC-NICKEL)				